

**Apraksts** **V r t ba**

**Visp r j inform cija:**

Produkta nosaukums:	UPS 25-60 N 180
Produkta Nr.:	96913085
EAN numurs:	5700313543465
Cena:	EUR 335.3

**Tehn.:**

trums Nr.:	3
Maksim lais spiedienaugstums:	60 dm
TF klase:	110
Apstiprin jumi pases datu pl ksn t :	CE,VDE,EAC,WEEE

**Materi li:**

S k a korpuss:	Ner s jošais t rauds
S k a korpuss:	DIN W.-Nr. 1.4301
Darbrats:	Kompoz ts, PES/PP

**Uzst d šana:**

Maks. apk rt j s vides temp. pie 80 C š idruma:	40 °C
Maksim lais darba spiediens:	10 b ri
Cauru u savienojums:	G 1 1/2
Spiediena pak pe:	PN 10
Garums no viena pievienojuma l dz otram:	180 mm

**Š idrums:**

S kn jamais š idrums:	dens
Š idruma temperat ras diapazons:	2 .. 110 °C
izv l t š idruma temperat ra:	60 °C
Bl vums pie izv l t s š idruma temperat ras:	983.2 kg/m³

**Elektriskie dati:**

leejas jauda 1. trum :	50 W
leejas jauda 2. trum :	55 W
Maks. pat r jam jauda:	60 W
T kla frekvence:	50 Hz
Nomin lais spriegums:	1 x 230 V
1. truma str va:	0.21 A
2. truma str va:	0.25 A
3. truma str va:	0.28 A
Kondensatora lielums - darb ba:	2.5 µF
Korpasa klase (IEC 34-5):	IP44
Izol cijas klase (IEC 85):	F
Motora aizsardz ba:	NAV
Termisk aizsardz ba:	Aizsardz ba p c tinumu pretest bas

**Kontrolē:**

Poz cijas piesl gk rba:	9H
-------------------------	----

**Citi:**

Neto svars:	2.9 kg
Bruto svars:	3.1 kg
Pieg des apjoms:	0.004 m³
Danish VVS No.:	380481061
Swedish RSK No.:	5803097
Finnish LVI No.:	4615616
Norwegian NRF no.:	9042215
Izcelsmes valsts:	RS
Muitas tarifa Nr.:	84137030

