



- Stainless steel pump body and motor shaft
- Double mechanical seal for great realibility, reduction of maintenance operations and continuos duty
- Integrated check valve
- 20 m safety rope

Model: SUB 8 S PLUS
Part number: N3200200
Barcode: 7630014536023

Submersible pump with asyncronous single phase motor, stainless steel pump body and stainless steel motor shaft. SUB 8S Plus has a double mechanical seal increasing the shaft resistence to stress due to the pump working.



APPLICATIONS

Irrigation of lawns and flowerbeds
Washing of terraces or outdoors floors
Basins or expansion tanks filling/draining

ABSORBED POWER	1100 W	POWER CABLE	22 m H07 RN8-F
VOLTAGE	230 V	SUCTION/DELIVERY PORT.	41.90 mm (1″1/4)
FLOW RATE	6000 l/h	MAX.WATER TEMPERATURE	40°C
PRESSURE/MAX.HEAD	57 m	WEIGHT	10.6 kg
RATED CURRENT	5 A	PACKAGING DIMENSIONS	74 x 19 x 16 cm
N° IMPELLERS	8	PCS PER PALLET	30
MIN.OPERATING SPACE	100 mm	ACCESSORIES	-
MAX.IMMERSION DEPTH	19 m		x 5



